


## Alem Track Lights















## Product Code: IK-RALEMTL-20W-27K-BL-90C-24D

| Voltage            | 100 - 277 V AC, 50-60 Hz |
|--------------------|--------------------------|
| Lumen Output       | 1753.61lm                |
| Power              | 20W                      |
| Efficacy           | 140lm/w                  |
| ССТ                | 2700K                    |
| CRI                | >90                      |
| Beam Angle         | 24°                      |
| Light Distribution | Medium                   |
| LED Type           | СОВ                      |
| LED Light Source   | Bridgelux V13            |
| Start Time         | Instant                  |
| Driver             | IK-LKAD029DC-05242       |
| Operating Position | Swiveling Type           |
| Dimming            | 0-10V                    |
| Construction       | Track                    |
| Mounting Type      | Track Light Structure    |
| Heads              | Single Head              |
| Body Material      | Aluminium Die cast       |
| Finish             | Black                    |
| Length             | 4-7/8"                   |
| Height             | 7"                       |
| Diameter           | 2-3/4"                   |
| Application Area   | Indoor Applications      |

| 3eam | Sprea                    | d (Options)                              | )  |   |  |  |  |
|------|--------------------------|--|--|---|--|--|--|
| Spot | 15°                      | Medium                                   | 24°  | Flood   | 38°  | Wide Flo   | od 60°   |
| ft   | Ø                        | ft                                       | Ø  | ft  | Ø  | ft   | Ø  |
| 3.0  | 0.72                     | 3.0                                      | 1.41   | 3.0   | 2.03   | 3.0  | 3.15   |
| 9.0  | 2.15                     | 9.0                                      | 4.22   | 9.0   | 6.09   | 9.0  | 9.45   |
| 15.0 | 3.58                     | 15.0                                     | 7.04   | 15.0  | 10.15  | 15.0   | 15.75  |
|      | Spot<br>ft<br>3.0<br>9.0 | Spot 15°<br>ft Ø<br>3.0 0.72<br>9.0 2.15 | Spot 15° Medium<br>ft Ø ft<br>3.0 0.72 3.0<br>9.0 2.15 9.0 | ft Ø ft Ø<br>3.0 0.72 3.0 1.41<br>9.0 2.15 9.0 4.22 | Spot 15* Medium 24* Flood   ft Ø ft Ø ft   3.0 0.72 3.0 1.41 3.0   9.0 2.15 9.0 4.22 9.0 | Spot 15° Medium 24° Flood 38°   ft Ø ft Ø ft Ø   3.0 0.72 3.0 1.41 3.0 2.03   9.0 2.15 9.0 4.22 9.0 6.09 | Spot 15° Medium 24° Flood 38° Wide Flo   ft Ø ft Ø ft Ø ft   3.0 0.72 3.0 1.41 3.0 2.03 3.0   9.0 2.15 9.0 4.22 9.0 6.09 9.0 |

Alem is a technologically advanced LED track light with incorporated electronic gear and chip on board.it also has a high-quality reflector with three different beam spreads. Moreover, the lamp housing of die-cast aluminium for optimal cooling allows the fixture to last longer than its traditional counterparts.

## **Technical Data**

IES File Link ±

Installation Instructions Link 🕹

