


## Alem Track Lights















## Product Code: IK-RALEMTL-30W-27K-BL-90C-15D

Voltage	100 - 277 V AC, 50-60 Hz		
Lumen Output	2579.8lm		
Power	30W		
Efficacy	140lm/w		
CCT	2700K		
CRI	>90		
Beam Angle	15°		
Light Distribution	Spot		
LED Type	СОВ		
LED Light Source	Bridgelux V13		
Start Time	Instant		
Driver	IK-LKAD029DC-05242		
Operating Position	Swiveling Type		
Dimming	0-10V		
Construction	Track		
Mounting Type	Track Light Structure		
Heads	Single Head		
Body Material	Aluminium Die cast		
Finish	Black		
Length	5-1/2"		
Height	7-3/4"		
Diameter	3-1/2"		
Application Area	Indoor Applications		

Beam Spread (Options)								
Spot	15°	Medium	24°	Flood	38°	Wide Fl	.00d 60°	
ft	Ø	ft	Ø	ft	Ø	ft	Ø	
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15	
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45	
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75	

Alem is a technologically advanced LED track light with incorporated electronic gear and chip on board.it also has a high-quality reflector with three different beam spreads. Moreover, the lamp housing of die-cast aluminium for optimal cooling allows the fixture to last longer than its traditional counterparts.

## **Technical Data**

IES File Link ±

Installation Instructions Link 🕹

