

Alem Track Lights

Technical Data Sheet

ITEM SKU#: 662187489469



Product Code : IK-RALEMTL-20W-40K-WH-90C-24D

| Voltage | 100 - 277 V AC, 50-60 Hz |
|--------------------|--------------------------|
| Lumen Output | 1913.52lm |
| Power | 20W |
| Efficacy | 140lm/w |
| ССТ | 4000K |
| CRI | >90 |
| Beam Angle | 24° |
| Light Distribution | Medium |
| LED Type | СОВ |
| LED Light Source | Bridgelux V13 |
| Start Time | Instant |
| Driver | IK-LKAD029DC-05242 |
| Operating Position | Swiveling Type |
| Dimming | 0-10V |
| Construction | Track |
| Mounting Type | Track Light Structure |
| Heads | Single Head |
| Body Material | Aluminium Die cast |
| Finish | White |
| Length | 4-7/8" |
| Height | 7" |
| Diameter | 2-3/4" |
| Application Area | Indoor Applications |
| | |

Technical Data

IES File Link 🛃

Installation Instructions Link 🕹

Alem is a technologically advanced LED track light with incorporated electronic gear and chip on board.It also has a high-quality reflector with three different beam spreads. Moreover, the lamp housing of die-cast aluminium for optimal cooling allows the fixture to last longer than its traditional counterparts.



retail@ikioledlighting.com I +1 844-533-4546 I www.retail.ikioledlighting.com

© IKIO LED LIGHTING 2024. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.

Spot

ft

3.0

9.0

15.0

Medium

ft

ø

0.72 3.0

2.15 9.0

3.58 15.0 <mark>24°</mark> Ø Flood

1.41

4.22

7.04

ft

3.0

9.0

15.0

38°

ø ft

2.03

6.09

10.15 15.0

Wide Flood 60

3.0

9.0

Ø

3.15

<mark>9.</mark>45

15.75