


Alem Track Lights

ITEM SKU#: 662187489742













Product Code: IK-RALEMTL-30W-30K-WH-90C-60D

Voltage	100 - 277 V AC, 50-60 Hz			
Lumen Output	2733.3lm			
Power	30W			
Efficacy	140lm/w			
ССТ	3000K			
CRI	>90			
Beam Angle	60°			
Light Distribution	Wide flood			
LED Type	COB			
LED Light Source	Bridgelux V13			
Start Time	Instant			
Driver	IK-LKAD029DC-05242			
Operating Position	Swiveling Type			
Dimming	0-10V			
Construction	Track			
Mounting Type	Track Light Structure			
Heads	Single Head			
Body Material	Aluminium Die cast			
Finish	White			
Length	5-1/2"			
Height	7-3/4"			
Diameter	3-1/2"			
Application Area	Indoor Applications			

3eam	Sprea	d (Options))				
Spot	15°	Medium	24°	Flood	38°	Wide Flo	od 60°
ft	Ø	ft	Ø	ft	Ø	ft	Ø
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75
	Spot ft 3.0 9.0	Spot 15° ft Ø 3.0 0.72 9.0 2.15	Spot 15° Medium ft Ø ft 3.0 0.72 3.0 9.0 2.15 9.0	ft Ø ft Ø 3.0 0.72 3.0 1.41 9.0 2.15 9.0 4.22	Spot 15* Medium 24* Flood ft Ø ft Ø ft 3.0 0.72 3.0 1.41 3.0 9.0 2.15 9.0 4.22 9.0	Spot 15° Medium 24° Flood 38° ft Ø ft Ø ft Ø 3.0 0.72 3.0 1.41 3.0 2.03 9.0 2.15 9.0 4.22 9.0 6.09	Spot 15° Medium 24° Flood 38° Wide Flo ft Ø ft Ø ft Ø ft 3.0 0.72 3.0 1.41 3.0 2.03 3.0 9.0 2.15 9.0 4.22 9.0 6.09 9.0

Alem is a technologically advanced LED track light with incorporated electronic gear and chip on board.It also has a high-quality reflector with three different beam spreads. Moreover, the lamp housing of die-cast aluminium for optimal cooling allows the fixture to last longer than its traditional counterparts.

Technical Data

IES File Link ±

Installation Instructions Link 🕹

