



Bolide Track Lights















Product Code: IK-RBOLIDETL-30W-40K-BL-90C-15D

Voltage	100 - 277 V AC, 50-60 Hz		
Lumen Output	2986.45lm		
Power	30W		
Efficacy	140lm/w		
CCT	4000K		
CRI	>90		
Beam Angle	15°		
Light Distribution	Spot		
LED Type	COB		
LED Light Source	Osram SOLERIQ S 19		
Start Time	Instant		
Driver	Stand Alone (included)		
Operating Position	Swiveling Type		
Dimming	Triac Dimming		
Construction	Track		
Mounting Type	Track Light Structure		
Heads	Single Head		
Finish	Black		
Length	4-5/8"		
Height	7-5/8"		
Diameter	3-1/2"		
Cut Out	7-3/8"		
Width (W)	7-3/8"		
Application Area	Indoor Applications		

Beam Spread (Options)							
Spot	15°	Medium	25°	Flood	36°	Wide Fl	.ood <mark>60°</mark>
ft	Ø	ft	Ø	ft	Ø	ft	Ø
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75

Bolide is a technologically advanced LED track light with incorporated electronic gear and chip on board. It also has a high-quality reflector with three different beam spreads. Moreover, the lamp housing of die-cast aluminum for optimal cooling allows the fixture to last longer than its traditional counterparts.

Technical Data

IES File Link <u>⊀</u>

Installation Instructions Link 🕹

