

Bolide Track Lights

Technical Data Sheet

ITEM SKU#: 662187489834



Product Code : IK-RBOLIDETL-30W-35K-BL-90C-24D

Voltage	100 - 277 V AC, 50-60 Hz
Lumen Output	2846.65lm
Power	30W
Efficacy	140lm/w
ССТ	3500K
CRI	>90
Beam Angle	24°
Light Distribution	Medium
LED Type	СОВ
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Operating Position	Swiveling Type
Dimming	Triac Dimming
Construction	Track
Mounting Type	Track Light Structure
Heads	Single Head
Finish	Black
Length	4-5/8"
Height	7-5/8"
Diameter	3-1/2"
Cut Out	7-3/8"
Width (W)	7-3/8"
Application Area	Indoor Applications

Beam Spread (Options)

Spot	15°	м	ediur	n	25°	Flood	36°	W	lide	Floo	od <mark>60°</mark>
ft	Ø	f	ť		Ø	ft	Ø		ťt		Ø
3.0	0.72	3	3.0		1.41	3.0	2.03	1	3.0		3.15
9.0	2.15	ç	9.0		4.22	9.0	6 .09	1	9.0		9.45
15.0	3.58	1	5.0		7.04	15.0	10.15	4	15.0		15.75

Bolide is a technologically advanced LED track light with incorporated electronic gear and chip on board. It also has a high-quality reflector with three different beam spreads. Moreover, the lamp housing of die-cast aluminum for optimal cooling allows the fixture to last longer than its traditional counterparts.

Technical Data

IES File Link 🕹

Installation Instructions Link 🛓



retail@ikioledlighting.com I +1 844-533-4546 I www.retail.ikioledlighting.com

© IKIO LED LIGHTING 2024. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.