

Bolide Track Lights

Technical Data Sheet

ITEM SKU#: 662187489896



Product Code : IK-RBOLIDETL-30W-30K-BL-90C-38D

Voltage	100 - 277 V AC, 50-60 Hz				
Lumen Output	2713.3lm				
Power	30W				
Efficacy	140lm/w				
ССТ	3000K				
CRI	>90				
Beam Angle	38°				
Light Distribution	Flood				
LED Type	СОВ				
LED Light Source	Osram SOLERIQ S 19				
Start Time	Instant				
Driver	Stand Alone (included)				
Operating Position	Swiveling Type				
Dimming	Triac Dimming				
Construction	Track				
Mounting Type	Track Light Structure				
Heads	Single Head				
Finish	Black				
Length	4-5/8"				
Height	7-5/8"				
Diameter	3-1/2"				
Cut Out	7-3/8"				
Width (W)	7-3/8"				
Application Area	Indoor Applications				

1

Beam Spread (Options)

Spot	15°	Medium	25°	Flood	36°	Wide Fl	ood 60°
ft	Ø	ft	Ø	ft	Ø	ft	Ø
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75

Bolide is a technologically advanced LED track light with incorporated electronic gear and chip on board. It also has a high-quality reflector with three different beam spreads. Moreover, the lamp housing of die-cast aluminum for optimal cooling allows the fixture to last longer than its traditional counterparts.

Technical Data

IES File Link 🕹

Installation Instructions Link 🛓



retail@ikioledlighting.com I +1 844-533-4546 I www.retail.ikioledlighting.com

© IKIO LED LIGHTING 2025. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.