

**Bolide Track Lights** 

## ITEM SKU#: 662187490052



## Product Code : IK-RBOLIDETL-30W-40K-WH-90C-15D

| Voltage            | 100 - 277 V AC, 50-60 Hz |
|--------------------|--------------------------|
| Lumen Output       | 2986.45lm                |
| Power              | 30W                      |
| Efficacy           | 140lm/w                  |
| ССТ                | 4000K                    |
| CRI                | >90                      |
| Beam Angle         | 15°                      |
| Light Distribution | Spot                     |
| LED Type           | СОВ                      |
| LED Light Source   | Osram SOLERIQ S 19       |
| Start Time         | Instant                  |
| Driver             | Stand Alone (included)   |
| Operating Position | Swiveling Type           |
| Dimming            | Triac Dimming            |
| Construction       | Track                    |
| Mounting Type      | Track Light Structure    |
| Heads              | Single Head              |
| Finish             | White                    |
| Length             | 4-5/8"                   |
| Height             | 7-5/8"                   |
| Diameter           | 3-1/2"                   |
| Cut Out            | 7-3/8"                   |
| Width (W)          | 7-3/8"                   |
| Application Area   | Indoor Applications      |
|                    |                          |

1

## Beam Spread (Options)

| Spot | 15°  | Medium | 25°  | Flood | 36°   | Wide Fl | .000 <mark>60°</mark> |
|------|------|--------|------|-------|-------|---------|-----------------------|
| ft   | Ø    | ft     | Ø    | ft    | Ø     | ft      | Ø                     |
| 3.0  | 0.72 | 3.0    | 1.41 | 3.0   | 2.03  | 3.0     | 3.15                  |
| 9.0  | 2.15 | 9.0    | 4.22 | 9.0   | 6.09  | 9.0     | 9.45                  |
| 15.0 | 3.58 | 15.0   | 7.04 | 15.0  | 10.15 | 15.0    | 15.75                 |

Bolide is a technologically advanced LED track light with incorporated electronic gear and chip on board. It also has a high-quality reflector with three different beam spreads. Moreover, the lamp housing of die-cast aluminum for optimal cooling allows the fixture to last longer than its traditional counterparts.

## **Technical Data**

IES File Link 🕹

Installation Instructions Link 🕹



retail@ikioledlighting.com I +1 844-533-4546 I www.retail.ikioledlighting.com

© IKIO LED LIGHTING 2024. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.