

Bolide Track Lights

ITEM SKU#: 662187490076



Product Code : IK-RBOLIDETL-30W-30K-WH-90C-24D

Voltage	100 - 277 V AC, 50-60 Hz			
Lumen Output	2711.1lm			
Power	30W			
Efficacy	140lm/w			
ССТ	3000K			
CRI	>90			
Beam Angle	24°			
Light Distribution	Medium			
LED Type	СОВ			
LED Light Source	Osram SOLERIQ S 19			
Start Time	Instant			
Driver	Stand Alone (included)			
Operating Position	Swiveling Type			
Dimming	Triac Dimming			
Construction	Track			
Mounting Type	Track Light Structure			
Heads	Single Head			
Finish	White			
Length	4-5/8"			
Height	7-5/8"			
Diameter	3-1/2"			
Cut Out	7-3/8"			
Width (W)	7-3/8"			
Application Area Indoor Applications				

Beam Spread (Options)

Beam Spread (Options)								
Spot	15°	Medium	25°	Flood	36°	Wide Fl	ood <mark>60°</mark>	
ft	Ø	ft	Ø	ft	Ø	ft	Ø	
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15	
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45	
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75	

Bolide is a technologically advanced LED track light with incorporated electronic gear and chip on board. It also has a high-quality reflector with three different beam spreads. Moreover, the lamp housing of die-cast aluminum for optimal cooling allows the fixture to last longer than its traditional counterparts.

Technical Data

IES File Link 🕹

Installation Instructions Link 🕹



retail@ikioledlighting.com I +1 844-533-4546 I www.retail.ikioledlighting.com

© IKIO LED LIGHTING 2025. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.