


Asparo Down Lights















Product Code: IK-RASPRODL-40W-40K-WH-90C-50D

Voltage	100 - 277 V AC, 50-60 Hz
Lumen Output	5320lm
Power	40W
Efficacy	140lm/w
CCT	4000K
CRI	>90
Beam Angle	50°
Light Distribution	Wide flood
LED Type	COB
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Operating Position	Non - Swiveling Type
Sporating (conton	Tion Chiveling Type
Dimming	On-Off / Triac / 0-10 V
Dimming	On-Off / Triac / 0-10 V
Dimming Construction	On-Off / Triac / 0-10 V Sqaure
Dimming Construction Mounting Type	On-Off / Triac / 0-10 V Sqaure Recessed
Dimming Construction Mounting Type Heads	On-Off / Triac / 0-10 V Sqaure Recessed Single Head
Dimming Construction Mounting Type Heads Body Material	On-Off / Triac / 0-10 V Sqaure Recessed Single Head Aluminium Die cast
Dimming Construction Mounting Type Heads Body Material Finish	On-Off / Triac / 0-10 V Sqaure Recessed Single Head Aluminium Die cast White
Dimming Construction Mounting Type Heads Body Material Finish Height	On-Off / Triac / 0-10 V Sqaure Recessed Single Head Aluminium Die cast White 3-3/4"
Dimming Construction Mounting Type Heads Body Material Finish Height Diameter	On-Off / Triac / 0-10 V Sqaure Recessed Single Head Aluminium Die cast White 3-3/4" 7-5/8"x7-5/8"

Beam Spread (Option)



Aspro, a square LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid /global connectors available with isolated LED Driver using Ultra bright OSRAM COB. Moreover, the specular darklight reflector in this store light allows outstanding visual comfort to the visitors.

