


# Gleam Down Lights

ITEM SKU#: 662187494166



## Product Code : IK-RGLEAMD-L-15W-40K-WH-90C-24D

Voltage	100 - 277 V AC, 50-60 Hz
Lumen Output	1479lm
Power	15W
Efficacy	140lm/w
CCT	4000K
CRI	>90
Beam Angle	24°
Light Distribution	Medium
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Operating Position	Swiveling Type
Dimming	On-Off / Triac / 0-10 V
Construction	Sqaure
Mounting Type	Recessed
Heads	Single Head
Body Material	Aluminium Die cast
Finish	White
Length	4-3/8"
Height	5-1/8"
Diameter	4"
Cut Out	4"x4"
Optics	Darklight Technology Black, Silver
Width (W)	4-3/8"
Application Area	Guest Room, Corridor, Restaurant, Meeting Room Club, Hall, Hotel Entrance

### Beam Spread (Options)

Spot	15°	Medium	24°	Flood	38°	Wide Flood	60°
3.0 ft	0.72	3.0	1.41	3.0	2.03	3.0	3.15
9.0 ft	2.15	9.0	4.22	9.0	6.09	9.0	9.45
15.0 ft	3.58	15.0	7.04	15.0	10.15	15.0	15.75

Gleam, a square shaped LED downlight is made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink that ensure high-durability. The specular darklight reflector in this store light allows outstanding visual comfort to the visitors so that they are able to explore the merchandise with ease.

## Technical Data

[IES File Link](#) ↓

[Installation Instructions Link](#) ↓