


Nova Down Lights

ITEM SKU#: 662187496405









	ССТ	3000K
	CRI	>90
	Beam Angle	36°
	Light Distribution	Flood
	LED Light Source	Osram SOLERIQ S 19
	Start Time	Instant
	Driver	Stand Alone (included)
	Operating Position	Swiveling Type, 360D
	Dimming	On-Off / Triac / 0-10 V
	Construction	Round
	Mounting Type	Recessed
	Heads	Single Head
	Body Material	Aluminium Die cast
	Finish	White
	Height	3-1/8"
	Diameter	3-1/2"
	Cut Out	3-1/8"

Darklight Technology Black, Silver

Ø 2.03

6.09

10.15

Product Code : IK-RNOVADL-12W-30K-WH-90C-36D

100 - 277 V AC, 50-60 Hz

1080lm 12W

90lm/w

Beam Spread (Options)							
pot	15°	Medium	24°	Flood			
ft	Ø	ft	Ø	ft			
~ ~	0.70			20			

9.0

4.22 9.0

7.04

15.0

Optics

9.0

15.0

Application Area

2.15

3.58 15.0


Voltage

Power Efficacy

Lumen Output

Nova, a round shaped LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. The specular darklight reflector in this store light allows outstanding visual comfort to the visitors so that they are able to explore the merchandise at ease.

Guest Room, Corridor, Restaurant, Meeting Room Club, Hall, Hotel Entrance



© IKIO LED LIGHTING 2024. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.