

## **Ocul Down Lights**

ITEM SKU#: 662187496764



## Product Code : IK-ROCULDL-08W-35K-WH-90C-24D

Voltage	100 - 277 V AC, 50-60 Hz				
Lumen Output	1330lm				
Power	8W				
Efficacy	140lm/w				
ССТ	3500K				
CRI	>90				
Beam Angle	24°				
Light Distribution	Medium				
LED Type	СОВ				
LED Light Source	Osram SOLERIQ S 19				
Start Time	Instant				
Driver	Stand Alone (included)				
Operating Position	Non - Swiveling Type				
Dimming	On-Off / Triac / 0-10 V				
Construction	Round				
Mounting Type	Recessed				
Heads	Single Head				
Body Material	Aluminium Die cast				
Finish	White				
Height	2-3/8"				
Diameter	3-1/2"				
Cut Out	3"				
Optics	Darklight Technology Black, Silver				
Application Area	Classroom, Meeting Room, Office, Club, Home				

## Beam Spread (Options)

	-						
Spot	15°	Medium	<b>24°</b>	Flood	36°	Wide Fl	.ood 60°
ft	Ø	ft	Ø	ft	Ø	ft	Ø
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75

Ocul, a round shaped LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid /global connectors available with isolated LED Driver using Ultra bright OSRAM COB.



retail@ikioledlighting.com I +1 844-533-4546 I www.retail.ikioledlighting.com

© IKIO LED LIGHTING 2025. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.