


Olivio Down Lights

Technical Data Sheet

ITEM SKU#: 662187498157





2700K CCT CRI >90 Beam Angle 15° Light Distribution Spot COB LED Type LED Light Source Osram SOLERIQ S 19 Start Time Instant Driver Stand Alone (included) **Operating Position** Non - Swiveling Type On-Off / Triac / 0-10 V Dimmina Construction Round Mounting Type Recessed Single Head Heads **Body Material** Aluminium Die cast Finish Black 4" Height 6-1/2" Diameter Cut Out 3"

Product Code : IK-ROLIVIODL-8W-27K-BL-90C-15D

100 - 277 V AC, 50-60 Hz

644.85lm 8W

140lm/w



Beam Spread (Options)

Application Area

Optics

Voltage

Power Efficacy

Lumen Output

Spot	15°	Medium	1 24°	Flood	38°	Wide Fl	ood <mark>60</mark> °
ft	Ø	ft	Ø	ft	Ø	ft	Ø
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75

Darklight Technology Black, Silver

Olivio, a round LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid /global connectors available with isolated LED Driver using Ultra bright OSRAM COB.

Guest Room, Corridor, Restaurant, Meeting Room Club, Hall, Hotel Entrance

Technical Data

IES File Link 🕹

Installation Instructions Link 🛓



retail@ikioledlighting.com I +1 844-533-4546 I www.retail.ikioledlighting.com

© IKIO LED LIGHTING 2024. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.