


Olivio Down Lights

ITEM SKU#: 662187498270













Product Code: IK-ROLIVIODL-8W-27K-BL-90C-60D

Voltage	100 - 277 V AC, 50-60 Hz
Lumen Output	622.09lm
Power	8W
Efficacy	140lm/w
CCT	2700K
CRI	>90
Beam Angle	60°
Light Distribution	Wide flood
LED Type	COB
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Onesetine Desition	Non-Curingling Time
Operating Position	Non - Swiveling Type
Dimming	On-Off / Triac / 0-10 V
Dimming	On-Off / Triac / 0-10 V
Dimming Construction	On-Off / Triac / 0-10 V Round
Dimming Construction Mounting Type	On-Off / Triac / 0-10 V Round Recessed
Dimming Construction Mounting Type Heads	On-Off / Triac / 0-10 V Round Recessed Single Head
Dimming Construction Mounting Type Heads Body Material	On-Off / Triac / 0-10 V Round Recessed Single Head Aluminium Die cast
Dimming Construction Mounting Type Heads Body Material Finish	On-Off / Triac / 0-10 V Round Recessed Single Head Aluminium Die cast Black
Dimming Construction Mounting Type Heads Body Material Finish Height	On-Off / Triac / 0-10 V Round Recessed Single Head Aluminium Die cast Black 4"
Dimming Construction Mounting Type Heads Body Material Finish Height Diameter	On-Off / Triac / 0-10 V Round Recessed Single Head Aluminium Die cast Black 4" 3-1/2"

Beam Spread (Options)								
Spot	15°	Medium	24°	Flood	38°	Wide Fl	ood 60°	
ft	Ø	ft	Ø	ft	Ø	ft	Ø	
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15	
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45	
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75	

Olivio, a round LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid /global connectors available with isolated LED Driver using Ultra bright OSRAM COB.

Technical Data

IES File Link <u>⊀</u>

Installation Instructions Link 🕹

