


Olivio Down Lights

Technical Data Sheet

ITEM SKU#: 662187498294





Light Distribution Wide flood LED Type COB LED Light Source Osram SOLERIQ S 19 Start Time Instant Driver Stand Alone (included) **Operating Position** Non - Swiveling Type On-Off / Triac / 0-10 V Dimmina Construction Round Mounting Type Recessed Single Head Heads **Body Material** Aluminium Die cast Finish Black 4" Height Diameter 3-1/2' Cut Out 3" Darklight Technology Black, Silver Optics

Guest Room, Corridor, Restaurant, Meeting Room Club, Hall, Hotel Entrance

Product Code : IK-ROLIVIODL-8W-35K-BL-90C-60D

100 - 277 V AC, 50-60 Hz

729.96lm 8W

140lm/w

3500K

>90

60°

CE



Beam Spread (Options)

Application Area

Voltage

Power Efficacy

CCT

CRI

Beam Angle

Lumen Output

Spot	15°	Medium	1 24°	Flood	38°	Wide Fl	ood <mark>60</mark> °
ft	Ø	ft	Ø	ft	Ø	ft	Ø
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75

Olivio, a round LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid /global connectors available with isolated LED Driver using Ultra bright OSRAM COB.

Technical Data

IES File Link 🛓

Installation Instructions Link 🛓



retail@ikioledlighting.com I +1 844-533-4546 I www.retail.ikioledlighting.com

© IKIO LED LIGHTING 2025. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.