

Olivio Down Lights

Technical Data Sheet

ITEM SKU#: 662187498683





Power	30W
Efficacy	140lm/w
CCT	2700K
CRI	>90
Beam Angle	24°
Light Distribution	Medium
LED Type	СОВ
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Operating Position	Non - Swiveling Type
Dimming	On-Off / Triac / 0-10 V
Construction	Round
Construction Mounting Type	Round Recessed
Mounting Type	Recessed
Mounting Type Heads	Recessed Single Head
Mounting Type Heads Body Material	Recessed Single Head Aluminium Die cast
Mounting Type Heads Body Material Finish	Recessed Single Head Aluminium Die cast Black
Mounting Type Heads Body Material Finish Height	Recessed Single Head Aluminium Die cast Black 5-5/8"
Mounting Type Heads Body Material Finish Height Diameter	Recessed Single Head Aluminium Die cast Black 5-5/8" 4-1/2"

1

Product Code : IK-ROLIVIODL-30W-27K-BL-90C-24D

100 - 277 V AC, 50-60 Hz

2444.66lm

Beam Spread (Options)

Voltage

Lumen Output

Spot	15°	Medium	24°	Flood	38°	Wide Fl	ood <mark>60°</mark>
ft	Ø	ft	Ø	ft	Ø	ft	Ø
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75

Olivio, a round LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid /global connectors available with isolated LED Driver using Ultra bright OSRAM COB.

Technical Data

IES File Link 🕹

Installation Instructions Link earrow



retail@ikioledlighting.com I +1 844-533-4546 I www.retail.ikioledlighting.com

© IKIO LED LIGHTING 2024. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.