

Olivio Down Lights

Technical Data Sheet

ITEM SKU#: 662187498874





CRI	>90
Beam Angle	24°
Light Distribution	Medium
LED Type	СОВ
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Operating Position	Non - Swiveling Type
Dimming	On-Off / Triac / 0-10 V
Construction	Round
Mounting Type	Recessed
Heads	Single Head
Body Material	Aluminium Die cast
Finish	Black
Height	6-5/8"
Diameter	5-1/8"
Cut Out	3"
Optics	Darklight Technology Black, Silver
Application Area	Guest Room, Corridor, Restaurant, Meeting Room Club, Hall, Hotel Entrance

1

Product Code : IK-ROLIVIODL-50W-30K-BL-90C-24D

100 - 277 V AC, 50-60 Hz

4263.3lm 50W

140lm/w

3000K

Beam Spread (Options)

Voltage

Power

Efficacy

CCT

Lumen Output

Spot		15°	Mediu	ım <mark>24°</mark>	Flood	38°	Wide F	lood 60°
ft		Ø	ft	Ø	ft	Ø	ft	Ø
3.0	0.	.72	3.0	1.41	3.0	2.03	3.0	3.15
9.0	2	.15	9.0	4.22	9.0	6.09	9.0	9.45
15.0	3.	.58	15.0	7.04	15 <mark>.0</mark>	10.15	15.0	15.75

Olivio, a round LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid /global connectors available with isolated LED Driver using Ultra bright OSRAM COB.

Technical Data

IES File Link 🕹

Installation Instructions Link 🕹



retail@ikioledlighting.com I +1 844-533-4546 I www.retail.ikioledlighting.com

© IKIO LED LIGHTING 2025. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.