


Olivio Down Lights















Product Code: IK-ROLIVIODL-30W-30K-WH-90C-24D

Voltage	100 - 277 V AC, 50-60 Hz				
Lumen Output	2566.9lm				
Power	30W				
Efficacy	140lm/w				
CCT	3000K				
CRI	>90				
Beam Angle	24°				
Light Distribution	Medium				
LED Type	СОВ				
LED Light Source	Osram SOLERIQ S 19				
Start Time	Instant				
Driver	Stand Alone (included)				
Operating Position	Non - Swiveling Type				
Dimming	On-Off / Triac / 0-10 V				
9					
Construction	Round				
-	Round Recessed				
Construction					
Construction Mounting Type	Recessed				
Construction Mounting Type Heads	Recessed Single Head				
Construction Mounting Type Heads Body Material	Recessed Single Head Aluminium Die cast				
Construction Mounting Type Heads Body Material Finish	Recessed Single Head Aluminium Die cast White				
Construction Mounting Type Heads Body Material Finish Height	Recessed Single Head Aluminium Die cast White 5-5/8"				
Construction Mounting Type Heads Body Material Finish Height Diameter	Recessed Single Head Aluminium Die cast White 5-5/8" 6-1/2"				

Beam Spread (Options)								
Spot	15°	Medium	24°	Flood	38°	Wide Fl	ood 60°	
ft	Ø	ft	Ø	ft	Ø	ft	Ø	
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15	
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45	
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75	

Olivio, a round LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid /global connectors available with isolated LED Driver using Ultra bright OSRAM COB.

Technical Data

IES File Link <u>⊀</u>

Installation Instructions Link 🕹

