


Thiea Down Lights

## ITEM SKU#: 662187500591





COB LED

DIMMABLE

IP20

Edition Output	111.01111
Power	8W
Efficacy	140lm/w
ССТ	3500K
CRI	>90
Beam Angle	38°
Light Distribution	Flood
LED Type	СОВ
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Operating Position	Non - Swiveling Type
Dimming	On-Off / Triac / 0-10 V
Construction	Sqaure
Mounting Type	Recessed
Heads	Single Head
Body Material	Aluminium Die cast
Finish	White
Length	2-7/8"
Height	4"
Cut Out	3"x3"
Optics	Darklight Technology Black, Silver
Width (W)	2-7/8"
Application Area	Guest Room, Corridor, Restaurant, Meeting Room Club, Hall, Hotel Entrance

## Product Code : IK-RTHEIADL-8W-35K-WH-90C-38D

100 - 277 V AC, 50-60 Hz

717.67lm

Voltage

Lumen Output

Beam Spread (Options)									
Spot	15°	Medium	24°	Flood	38°	Wide Fl	ood 60°		
ft	Ø	ft	Ø	ft	Ø	ft	Ø		
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15		
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45		
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75		

Theia, a square LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid (global connectors available with isolated LED Driver using Ultra bright OSRAM COB.

## Technical Data

IES File Link 🛃

retail@ikioledlighting.com I +1 844-533-4546 I www.retail.ikioledlighting.com

© IKIO LED LIGHTING 2025. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.

