


Thiea Down Lights

ITEM SKU#: 662187500607













Product Code: IK-RTHEIADL-8W-40K-WH-90C-38D

Lumen Output 753.55lm Power 8W Efficacy 140lm/w CCT 4000K CRI >90 Beam Angle 38° Light Distribution Flood LED Type COB LED Light Source Osram SOLERIQ S 19 Start Time Instant Driver Stand Alone (included) Operating Position Non - Swiveling Type Dimming On-Off / Triac / 0-10 V Construction Sqaure Mounting Type Recessed Heads Single Head Body Material Aluminium Die cast Finish White Length 2-7/8" Height 4" Cut Out 3"x3" Optics Darklight Technology Black, Silver Width (W) 2-7/8" Application Area Guest Room, Corridor, Restaurant, Meeting Room Club, Hall, Hotel Entrance	Voltage	100 - 277 V AC, 50-60 Hz
Efficacy 140Im/w CCT 4000K CRI >90 Beam Angle 38° Light Distribution Flood LED Type COB LED Light Source Osram SOLERIQ S 19 Start Time Instant Driver Stand Alone (included) Operating Position Non - Swiveling Type Dimming On-Off / Triac / 0-10 V Construction Sqaure Mounting Type Recessed Heads Single Head Body Material Aluminium Die cast Finish White Length 2-7/8" Height 4" Cut Out 3"x3" Optics Darklight Technology Black, Silver Withth (W) 2-7/8"	Lumen Output	753.55lm
CCT 4000K CRI >90 Beam Angle 38° Light Distribution Flood LED Type COB LED Light Source Osram SOLERIQ S 19 Start Time Instant Driver Stand Alone (included) Operating Position Non - Swiveling Type Dimming On-Off / Triac / 0-10 V Construction Sqaure Mounting Type Recessed Heads Single Head Body Material Aluminium Die cast Finish White Length 4" Cut Out 3"x3" Optics Darklight Technology Black, Silver Width (W) 2-7/8"	Power	8W
CRI >90 Beam Angle 38° Light Distribution Flood LED Type COB LED Light Source Osram SOLERIQ S 19 Start Time Instant Driver Stand Alone (included) Operating Position Non - Swiveling Type Dimming On-Off / Triac / 0-10 V Construction Sqaure Mounting Type Recessed Heads Single Head Body Material Aluminium Die cast Finish White Length 2-7/8" Height 4" Cut Out 3"x3" Optics Darklight Technology Black, Silver Width (W) 2-7/8"	Efficacy	140lm/w
Beam Angle 38° Light Distribution Flood LED Type COB LED Light Source Osram SOLERIQ S 19 Start Time Instant Driver Stand Alone (included) Operating Position Non - Swiveling Type Dimming On-Off / Triac / 0-10 V Construction Sqaure Mounting Type Recessed Heads Single Head Body Material Aluminium Die cast Finish White Length 2-7/8" Height 4" Cut Out 3"x3" Optics Darklight Technology Black, Silver Width (W) 2-7/8"	CCT	4000K
Light Distribution Flood LED Type COB LED Light Source Osram SOLERIQ S 19 Start Time Instant Driver Stand Alone (included) Operating Position Non - Swiveling Type Dimming On-Off / Triac / 0-10 V Construction Sqaure Mounting Type Recessed Heads Single Head Body Material Aluminium Die cast Finish White Length 2-7/8" Height 4" Cut Out 3"x3" Optics Darklight Technology Black, Silver Width (W) 2-7/8"	CRI	>90
LED Type COB LED Light Source Osram SOLERIQ S 19 Start Time Instant Driver Stand Alone (included) Operating Position Non - Swiveling Type Dimming On-Off / Triac / 0-10 V Construction Sqaure Mounting Type Recessed Heads Single Head Body Material Aluminium Die cast Finish White Length 2-7/8" Height 4" Cut Out 3"x3" Optics Darklight Technology Black, Silver Width (W) 2-7/8"	Beam Angle	38°
LED Light SourceOsram SOLERIQ S 19Start TimeInstantDriverStand Alone (included)Operating PositionNon - Swiveling TypeDimmingOn-Off / Triac / 0-10 VConstructionSqaureMounting TypeRecessedHeadsSingle HeadBody MaterialAluminium Die castFinishWhiteLength2-7/8"Height4"Cut Out3"x3"OpticsDarklight Technology Black, SilverWidth (W)2-7/8"	Light Distribution	Flood
Start Time Instant Driver Stand Alone (included) Operating Position Non - Swiveling Type Dimming On-Off / Triac / 0-10 V Construction Sqaure Mounting Type Recessed Heads Single Head Body Material Aluminium Die cast Finish White Length 2-7/8" Height 4" Cut Out 3"x3" Optics Darklight Technology Black, Silver Width (W) 2-7/8"	LED Type	COB
Driver Stand Alone (included) Operating Position Non - Swiveling Type Dimming On-Off / Triac / 0-10 V Construction Sqaure Mounting Type Recessed Heads Single Head Body Material Aluminium Die cast Finish White Length 2-7/8" Height 4" Cut Out 3"x3" Optics Darklight Technology Black, Silver Width (W) 2-7/8"	LED Light Source	Osram SOLERIQ S 19
Operating PositionNon - Swiveling TypeDimmingOn-Off / Triac / 0-10 VConstructionSqaureMounting TypeRecessedHeadsSingle HeadBody MaterialAluminium Die castFinishWhiteLength2-7/8"Height4"Cut Out3"x3"OpticsDarklight Technology Black, SilverWidth (W)2-7/8"	Start Time	Instant
Dimming On-Off / Triac / 0-10 V Construction Sqaure Mounting Type Recessed Heads Single Head Body Material Aluminium Die cast Finish White Length 2-7/8" Height 4" Cut Out 3"x3" Optics Darklight Technology Black, Silver Width (W) 2-7/8"	Driver	Stand Alone (included)
Construction Sqaure Mounting Type Recessed Heads Single Head Body Material Aluminium Die cast Finish White Length 2-7/8" Height 4" Cut Out 3"x3" Optics Darklight Technology Black, Silver Width (W) 2-7/8"	Operating Position	Non - Swiveling Type
Mounting Type Recessed Heads Single Head Body Material Aluminium Die cast Finish White Length 2-7/8" Height 4" Cut Out 3"x3" Optics Darklight Technology Black, Silver Width (W) 2-7/8"	Dimming	On-Off / Triac / 0-10 V
Heads Single Head Body Material Aluminium Die cast Finish White Length 2-7/8" Height 4" Cut Out 3"x3" Optics Darklight Technology Black, Silver Width (W) 2-7/8"	Construction	Sqaure
Body Material Aluminium Die cast Finish White Length 2-7/8" Height 4" Cut Out 3"x3" Optics Darklight Technology Black, Silver Width (W) 2-7/8"	Mounting Type	Recessed
Finish White Length 2-7/8" Height 4" Cut Out 3"x3" Optics Darklight Technology Black, Silver Width (W) 2-7/8"	Heads	Single Head
Length 2-7/8" Height 4" Cut Out 3"x3" Optics Darklight Technology Black, Silver Width (W) 2-7/8"	Body Material	Aluminium Die cast
Height 4" Cut Out 3"x3" Optics Darklight Technology Black, Silver Width (W) 2-7/8"	Finish	White
Cut Out 3"x3" Optics Darklight Technology Black, Silver Width (W) 2-7/8"	Length	2-7/8"
Optics Darklight Technology Black, Silver Width (W) 2-7/8"	Height	4"
Width (W) 2-7/8"	Cut Out	3"x3"
	Optics	Darklight Technology Black, Silver
Application Area Guest Room, Corridor, Restaurant, Meeting Room Club, Hall, Hotel Entrance	Width (W)	2-7/8"
	Application Area	Guest Room, Corridor, Restaurant, Meeting Room Club, Hall, Hotel Entrance

Beam Spread (Options)									
Spot	15°	Medium	24°	Flood	38°	Wide Fl	ood 60°		
ft	Ø	ft	Ø	ft	Ø	ft	Ø		
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15		
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45		
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75		

Theia, a square LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid (global connectors available with isolated LED Driver using Ultra bright OSRAM COB.

Technical Data

IES File Link 丛

