


Thiea Down Lights

## ITEM SKU#: 662187500614







Voltage	100 - 277 V AC, 50-60 Hz
Lumen Output	662.09lm
Power	8W
Efficacy	140lm/w
ССТ	2700K
CRI	>90
Beam Angle	60°
Light Distribution	Wide flood
LED Type	СОВ
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Operating Position	Non - Swiveling Type
Dimming	On-Off / Triac / 0-10 V
Construction	Sqaure
Mounting Type	Recessed
Heads	Single Head
Body Material	Aluminium Die cast
Finish	White
Length	2-7/8"
Height	4"
Cut Out	3"x3"
Optics	Darklight Technology Black, Silver
Width (W)	2-7/8"
Application Area	Guest Room, Corridor, Restaurant, Meeting Room Club, Hall, Hotel Entrance

Product Code : IK-RTHEIADL-8W-27K-WH-90C-60D

Beam Spread (options)									
Spot	15°	Medium	24°	Flood	38°	Wide Fl	.ood 60°		
ft	Ø	ft	Ø	ft	Ø	ft	Ø		
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15		
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45		
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75		

Theia, a square LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid / global connectors available with isolated LED Driver using Ultra bright OSRAM COB.

## Technical Data

IES File Link 🕹

retail@ikioledlighting.com I +1 844-533-4546 I www.retail.ikioledlighting.com

© IKIO LED LIGHTING 2024. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.