


Optik Track Lights

ITEM SKU#: 662187490403













Product Code: IK-ROPTIKTL-30W-30K-WH-90C-ADB

Voltage	100 - 277 V AC, 50-60 Hz
Lumen Output	4200lm
Power	30W
Efficacy	140lm/w
ССТ	3000K
CRI	>90
Beam Angle	15°
Light Distribution	Wide flood
LED Type	COB
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Built in
Operating Position	Swiveling Type
Dimming	Triac Dimming
Construction	Track
Mounting Type	Track Light Structure
Heads	Single Head
Body Material	Aluminium Die cast
Finish	White
Length	7-1/8"
Height	7-1/4"
Diameter	3"
Application Area	Indoor Applications

Beam	Sprea	d (Options	;)				
Spot	15°	Medium	24°	Flood	36°	Wide Flo	ood 60°
ft	Ø	ft	Ø	ft	Ø	ft	Ø
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75
	Spot ft 3.0 9.0	Spot 15° ft Ø 3.0 0.72 9.0 2.15	Spot 15° Medium ft Ø ft 3.0 0.72 3.0 9.0 2.15 9.0	ft Ø ft Ø 3.0 0.72 3.0 1.41 9.0 2.15 9.0 4.22	Spot 15° Medium 24° Flood ft Ø ft Ø ft 3.0 0.72 3.0 1.41 3.0 9.0 2.15 9.0 4.22 9.0	Spot 15* Medium 24* Flood 36* ft Ø ft Ø ft Ø 3.0 0.72 3.0 1.41 3.0 2.03 9.0 2.15 9.0 4.22 9.0 6.09	Spot 15' Medium 24' Flood 36' Wide Flo ft Ø ft Ø ft Ø ft 3.0 0.72 3.0 1.41 3.0 2.03 3.0 9.0 2.15 9.0 4.22 9.0 6.09 9.0

Optik is a technologically advanced LED track light with incorporated electronic gear and chip on board. It also has a high-quality reflector with three different beam spreads. Moreover, the lamp housing of die-cast aluminum for optimal cooling allows the fixture to last longer than its traditional counterparts.

Technical Data

IES File Link 丛

Installation Instructions Link 🕹

