


# Aurora Pendant Lights

ITEM SKU#: 662187503394



## Product Code : IK-RAuroraPL-40W-40K-WH-90C-30D

|                    |  |
|--------------------|--|
| Voltage            | 100 - 277 V AC, 50-60 Hz   |
| Lumen Output       | 3600lm   |
| Power              | 40W  |
| CCT                | 4000K  |
| CRI                | >90  |
| Beam Angle         | 30°  |
| Light Distribution | Medium   |
| LED Light Source   | Osram SOLERIQ S 19   |
| Start Time         | Instant  |
| Driver             | Stand Alone (included)   |
| Operating Position | No Swiveling Type  |
| Dimming            | Triac Dimming / 0-10 V Dimming                                   |
| Heads              | Single Head  |
| Finish             | White  |
| Height             | 6-1/4"   |
| Diameter           | 5-5/8"   |
| Optics             | Reflective Cup Structure   |
| Application Area   | Guest Room, Restaurant, Meeting Room, Club, Hall, Hotel Entrance |

### Beam Spread (Options)

| Spot | 15°  |   | Medium |      | 30° |      | Flood |   | 45° |   |
|------|------|---|--------|------|-----|------|-------|---|-----|---|
|      | ft   | Ø | ft     | Ø    | ft  | Ø    | ft    | Ø | ft  | Ø |
| 3.0  | 0.72 |   | 3.0    | 1.41 |     | 3.0  | 2.03  |   |     |   |
| 9.0  | 2.15 |   | 9.0    | 4.22 |     | 9.0  | 6.09  |   |     |   |
| 15.0 | 3.58 |   | 15.0   | 7.04 |     | 15.0 | 10.15 |   |     |   |

Aurora is a technologically advanced LED Pendant Light that incorporates electronic gear and a high-quality lens with wide beam spread. While commonly used as task light, the unique and state-of-the-art design of this luminaire also enhances the overall aesthetics of your store.

