


Aurora Pendant Lights

ITEM SKU#: 662187503943













Product Code: IK-RAuroraPL-12W-40K-WH-90C-45D

| Voltage | 100 - 277 V AC, 50-60 Hz | | | | |
|-----------------------------|---|--|--|--|--|
| Lumen Output | 1080lm | | | | |
| Power | 12W | | | | |
| ССТ | 4000K | | | | |
| CRI | >90 | | | | |
| Beam Angle | 45° | | | | |
| Light Distribution | Flood | | | | |
| LED Light Source | Osram SOLERIQ S 19 | | | | |
| Start Time | Instant | | | | |
| Driver | Stand Alone (included) | | | | |
| | | | | | |
| Operating Position | No Swiveling Type | | | | |
| Operating Position Dimming | No Swiveling Type Triac Dimming / 0-10 V Dimming | | | | |
| | | | | | |
| Dimming | Triac Dimming / 0-10 V Dimming | | | | |
| Dimming Heads | Triac Dimming / 0-10 V Dimming Single Head | | | | |
| Dimming Heads Finish | Triac Dimming / 0-10 V Dimming Single Head White | | | | |
| Dimming Heads Finish Height | Triac Dimming / 0-10 V Dimming Single Head White 5-7/8" | | | | |

| Beam Spread (Options) | | | | | | | |
|-----------------------|------|--------|------|-------|------|--|--|
| Spot | 15° | Medium | 30° | Flood | 45° | | |
| ft | Ø | ft | Ø | ft | Ø | | |
| 3.0 | 0.72 | 3.0 | 1.41 | 3.0 | 2.03 | | |

4.22 9.0

6.09

2.15 9.0

3.58

Aurora is a technologically advanced LED Pendant Light that incorporates electronic gear and a high-quality lens with wide beam spread. While commonly used as task light, the unique and state-of-the-art design of this luminaire also enhances the overall aesthetics of your store.

