


EOS Pendant Lights

ITEM SKU#: 662187505220



COB LED


Product Code : IK-REosPL-20W-50K-WH-90C-45D

Voltage	100 - 277 V AC, 50-60 Hz
Lumen Output	1900lm
Power	20W
ССТ	5000K
CRI	>90
Beam Angle	45°
Light Distribution	Flood
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Operating Position	No Swiveling Type
Dimming	Triac Dimming / 0-10 V Dimming
Heads	Single Head
Finish	White
Length	3-3/4"
Height	5-7/8"
Optics	Reflective Cup Structure
Width (W)	3-3/4"
Application Area	Guest Room, Restaurant, Meeting Room, Club, Hall, Hotel Entrance

Beam Spread (Options)

	beam Spread (options)			
Spot <mark>15°</mark> Medium <mark>30°</mark> Flood	45°			
ft Ø ft Ø ft	Ø			
3.0 0.72 3.0 1.41 3.0 2	2.03			
9.0 2.15 9.0 4.22 9.0 6	6.09			
15.0 3.58 15.0 7.04 15.0 10	0.15			

Eos is a technologically advanced LED Pendant Light that incorporates electronic gear and a high-quality lens with wide beam spread. While commonly used as task light, the unique and state-of-the-art design of this luminaire also enhances the overall aesthetics of your store.



DIMMABLE

IP20



© IKIO LED LIGHTING 2024. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.