


Mica Pendant Lights

ITEM SKU#: 662187506708













Product Code: IK-RMicaPL-40W-27K-WH-90C-15D

Voltage 100 - 277 V AC, 50-60 Hz Lumen Output 3200Im Power 40W CCT 2700K CRI >90 Beam Angle 15° Light Distribution Spot LED Light Source Osram SOLERIQ S 19 Start Time Instant Driver Stand Alone (included) Operating Position No Swiveling Type Dimming Triac Dimming / 0-10 V Dimmin Heads Single Head Finish White Length 6-1/4" Height 6-1/2" Optics Reflective Cup Structure Width (W) 6-1/4" Application Area Guest Room, Restaurant, Mee	
Power 40W CCT 2700K CRI >90 Beam Angle 15° Light Distribution Spot LED Light Source Osram SOLERIQ S 19 Start Time Instant Driver Stand Alone (included) Operating Position No Swiveling Type Dimming Triac Dimming / 0-10 V Dimmin Heads Single Head Finish White Length 6-1/4" Height 6-1/2" Optics Reflective Cup Structure Width (W) 6-1/4"	
CCT 2700K CRI >90 Beam Angle 15° Light Distribution Spot LED Light Source Osram SOLERIQ S 19 Start Time Instant Driver Stand Alone (included) Operating Position No Swiveling Type Dimming Triac Dimming / 0-10 V Dimmin Heads Single Head Finish White Length 6-1/4" Height 6-1/2" Optics Reflective Cup Structure Width (W) 6-1/4"	
CRI >90 Beam Angle 15° Light Distribution Spot LED Light Source Osram SOLERIQ S 19 Start Time Instant Driver Stand Alone (included) Operating Position No Swiveling Type Dimming Triac Dimming / 0-10 V Dimmin Heads Single Head Finish White Length 6-1/4" Height 6-1/2" Optics Reflective Cup Structure Width (W) 6-1/4"	
Beam Angle 15° Light Distribution Spot LED Light Source Osram SOLERIQ S 19 Start Time Instant Driver Stand Alone (included) Operating Position No Swiveling Type Dimming Triac Dimming / 0-10 V Dimmin Heads Single Head Finish White Length 6-1/4" Height 6-1/2" Optics Reflective Cup Structure Width (W) 6-1/4"	
Light Distribution Spot LED Light Source Osram SOLERIQ S 19 Start Time Instant Driver Stand Alone (included) Operating Position No Swiveling Type Dimming Triac Dimming / 0-10 V Dimmin Heads Single Head Finish White Length 6-1/4" Height 6-1/2" Optics Reflective Cup Structure Width (W) 6-1/4"	
LED Light Source Osram SOLERIQ S 19 Start Time Instant Driver Stand Alone (included) Operating Position No Swiveling Type Dimming Triac Dimming / 0-10 V Dimmin Heads Single Head Finish White Length 6-1/4" Height 6-1/2" Optics Reflective Cup Structure Width (W) 6-1/4"	
Start Time Instant Driver Stand Alone (included) Operating Position No Swiveling Type Dimming Triac Dimming / 0-10 V Dimmin Heads Single Head Finish White Length 6-1/4" Height 6-1/2" Optics Reflective Cup Structure Width (W) 6-1/4"	
Driver Stand Alone (included) Operating Position No Swiveling Type Dimming Triac Dimming / 0-10 V Dimmin Heads Single Head Finish White Length 6-1/4" Height 6-1/2" Optics Reflective Cup Structure Width (W) 6-1/4"	
Operating Position No Swiveling Type Dimming Triac Dimming / 0-10 V Dimmin Heads Single Head Finish White Length 6-1/4" Height 6-1/2" Optics Reflective Cup Structure Width (W) 6-1/4"	
Dimming Triac Dimming / 0-10 V Dimming Heads Single Head Finish White Length 6-1/4" Height 6-1/2" Optics Reflective Cup Structure Width (W) 6-1/4"	
Heads Single Head Finish White Length 6-1/4" Height 6-1/2" Optics Reflective Cup Structure Width (W) 6-1/4"	
Finish White Length 6-1/4" Height 6-1/2" Optics Reflective Cup Structure Width (W) 6-1/4"	ing
Length 6-1/4" Height 6-1/2" Optics Reflective Cup Structure Width (W) 6-1/4"	
Height 6-1/2" Optics Reflective Cup Structure Width (W) 6-1/4"	
Optics Reflective Cup Structure Width (W) 6-1/4"	
Width (W) 6-1/4"	
Application Area Guest Room, Restaurant, Mee	
	eting Room, Club, Hall, Hotel Entrance

Spot	15°	Medium	30°	Flood	45°
ft	Ø	ft	Ø	ft	Ø
3.0	0.72	3.0	1.41	3.0	2.03
9.0	2.15	9.0	4.22	9.0	6.09
15.0	3.58	15.0	7.04	15.0	10.15

Mica is a technologically advanced LED Pendant Light that incorporates electronic gear and a high-quality lens with wide beam spread. While commonly used as task light, the unique and state-of-the-art design of this luminaire also enhances the overall aesthetics of your store.

