

Remus Pendant Lights

ITEM SKU#: 662187507347



CE

COB LED

DIMMABLE

Product Code : IK-RRemusPL-20W-40K-WH-90C-24D

| Voltage | 100 - 277 V AC, 50-60 Hz |
|--------------------|--|
| Lumen Output | 2000lm |
| Power | 20W |
| ССТ | 4000K |
| CRI | >90 |
| Beam Angle | 24° |
| Light Distribution | Medium |
| LED Light Source | Osram SOLERIQ S 19 |
| Start Time | Instant |
| Driver | Stand Alone (included) |
| Operating Position | Swiveling Type |
| Dimming | Triac Dimming |
| Heads | Single Head |
| Finish | White |
| Height | 6-5/8" |
| Diameter | 3-1/8" |
| Application Area | Guest Room, Restaurant, Meeting Room, Club, Hall, Hotel Entrance |

Beam Spread (Options)

٥

IP20

| Spot 11° | | Medium | | 24° Flood | | 30° | | | |
|----------|--|--------|------|-----------|------|------|-------|--|--|
| ft | | Ø | ft | | Ø | ft | Ø | | |
| 3.0 | | 0.72 | 3.0 | | 1.41 | 3.0 | 2.03 | | |
| 9.0 | | 2.15 | 9.0 | | 4.22 | 9.0 | 6.09 | | |
| 15.0 | | 3.58 | 15.0 | | 7.04 | 15.0 | 10.15 | | |

Remus is a technologically advanced LED Pendant Light that incorporates electronic gear and a high-quality lens with different beam spread. While commonly used as task light, the unique and state-of-the-art design of this luminaire also enhances the overall aesthetics of your store.

retail@ikioledlighting.com I +1 844-533-4546 I www.retail.ikioledlighting.com

© IKIO LED LIGHTING 2024. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.