


Prime Track Lights

ITEM SKU#: 662187490670













Product Code: IK-RPRIMETL-20W-27K-BL-90C-38D

| Voltage | 100 - 277 V AC, 50-60 Hz |
|--------------------|--------------------------|
| Lumen Output | 1732.47lm |
| Power | 20W |
| Efficacy | 140lm/w |
| ССТ | 2700K |
| CRI | >90 |
| Beam Angle | 38° |
| Light Distribution | Flood |
| LED Type | COB |
| LED Light Source | Osram SOLERIQ S 19 |
| Start Time | Instant |
| Driver | Stand Alone (included) |
| Operating Position | Swiveling Type |
| Dimming | Triac Dimming |
| Construction | Track |
| Mounting Type | Track Light Structure |
| Heads | Single Head |
| Body Material | Aluminium Die cast |
| Finish | Black |
| Length | 4-3/8" |
| Height | 8-1/4" |
| Diameter | 3-1/8" |
| Application Area | Indoor Applications |
| | |

| Dean | Sprea | U (Options | 5) | | | |
|------|-------------------|------------------------------|--------------------------------------|--------------------------------|--|---|
| Spot | 11° | Medium | 24° | Flood | | 3 |
| ft | Ø | ft | Ø | ft | | |
| 3.0 | 0.72 | 3.0 | 1.41 | 3.0 | A : | 2.0 |
| 9.0 | 2.15 | 9.0 | 4.22 | 9.0 | | 6.0 |
| | Spot ft 3.0 | Spot 11° ft Ø 3.0 0.72 | Spot 11° Medium ft Ø ft 3.0 0.72 3.0 | ft Ø ft Ø 3.0 0.72 3.0 1.41 | Spot 11° Medium 24° Flood ft Ø ft Ø ft 3.0 0.72 3.0 1.41 3.0 | Spot 11° Medium 24° Flood ft Ø ft 3.0 0.72 3.0 1.41 3.0 |

Prime is a technologically advanced LED track light with incorporated electronic gear and chip on board. It also has a high-quality reflector with three different beam spreads. Moreover, the lamp housing of die-cast aluminum for optimal cooling allows the fixture to last longer than its traditional counterparts.

Technical Data

IES File Link ±

Installation Instructions Link 🕹

