


## **Prime Track Lights**

ITEM SKU#: 662187490847













## Product Code: IK-RPRIMETL-20W-40K-WH-90C-38D

| Voltage            | 100 - 277 V AC, 50-60 Hz |
|--------------------|--------------------------|
| Lumen Output       | 2005.55lm                |
| Power              | 20W                      |
| Efficacy           | 140lm/w                  |
| CCT                | 4000K                    |
| CRI                | >90                      |
| Beam Angle         | 38°                      |
| Light Distribution | Flood                    |
| LED Type           | COB                      |
| LED Light Source   | Osram SOLERIQ S 19       |
| Start Time         | Instant                  |
| Driver             | Stand Alone (included)   |
| Operating Position | Swiveling Type           |
| Dimming            | Triac Dimming            |
| Construction       | Track                    |
| Mounting Type      | Track Light Structure    |
| Heads              | Single Head              |
| Body Material      | Aluminium Die cast       |
| Finish             | White                    |
| Length             | 4-3/8"                   |
| Height             | 8-1/4"                   |
| Diameter           | 3-1/8"                   |
| Application Area   | Indoor Applications      |
|                    |                          |

| Dearn Opicaa (options) |      |        |      |       |     |  |
|------------------------|------|--------|------|-------|-----|--|
| Spot                   | 11°  | Medium | 24°  | Flood | 3   |  |
| ft                     | Ø    | ft     | Ø    | ft    |     |  |
| 3.0                    | 0.72 | 3.0    | 1.41 | 3.0   | 2.0 |  |
| 9.0                    | 2.15 | 9.0    | 4.22 | 9.0   | 6.0 |  |

Prime is a technologically advanced LED track light with incorporated electronic gear and chip on board. It also has a high-quality reflector with three different beam spreads. Moreover, the lamp housing of die-cast aluminum for optimal cooling allows the fixture to last longer than its traditional counterparts.

## **Technical Data**

IES File Link <u>⊀</u>

Installation Instructions Link extstyle ex

