


## **Trang Track Lights**

ITEM SKU#: 662187491059













## Product Code: IK-RTRANGTL-7W-27K-BL-90C-24D

Voltage	100 - 277 V AC, 50-60 Hz			
Lumen Output	547.14lm			
Power	7W			
Efficacy	140lm/w			
ССТ	2700K			
CRI	>90			
Beam Angle	24°			
Light Distribution	Medium			
LED Type	COB			
LED Light Source	Osram SOLERIQ S 19			
Start Time	Instant			
Driver	Stand Alone (included)			
Operating Position	Swiveling Type			
Dimming	Triac Dimming			
Construction	Track			
Mounting Type	Track Light Structure			
Heads	Single Head			
Body Material	Aluminium Die cast			
Finish	Black			
Length	5-3/8"			
Height	5-7/8"			
Diameter	2"			
Application Area	Indoor Applications			

3eam	Sprea	d (Options)	)				
Spot	15°	Medium	24°	Flood	38°	Wide Flo	od 60°
ft	Ø	ft	Ø	ft	Ø	ft	Ø
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75
	Spot ft 3.0 9.0	Spot 15° ft Ø 3.0 0.72 9.0 2.15	Spot 15° Medium ft Ø ft 3.0 0.72 3.0 9.0 2.15 9.0	ft Ø ft Ø 3.0 0.72 3.0 1.41 9.0 2.15 9.0 4.22	Spot 15* Medium 24* Flood   ft Ø ft Ø ft   3.0 0.72 3.0 1.41 3.0   9.0 2.15 9.0 4.22 9.0	Spot 15° Medium 24° Flood 38°   ft Ø ft Ø ft Ø   3.0 0.72 3.0 1.41 3.0 2.03   9.0 2.15 9.0 4.22 9.0 6.09	Spot 15° Medium 24° Flood 38° Wide Flo   ft Ø ft Ø ft Ø ft   3.0 0.72 3.0 1.41 3.0 2.03 3.0   9.0 2.15 9.0 4.22 9.0 6.09 9.0

Trang is a technologically advanced LED track light with incorporated electronic gear and chip on board. It also has a high-quality reflector with three different beam spreads. Moreover, the lamp housing of die-cast aluminum for optimal cooling allows the fixture to last longer than its traditional counterparts.

## **Technical Data**

IES File Link 丛

Installation Instructions Link 🕹

