


## **Trang Track Lights**

ITEM SKU#: 662187491363













## Product Code: IK-RTRANGTL-20W-30K-BL-90C-15D

Voltage	100 - 277 V AC, 50-60 Hz
Lumen Output	1831.1lm
Power	20W
Efficacy	140lm/w
CCT	3000K
CRI	>90
Beam Angle	15°
Light Distribution	Spot
LED Type	COB
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Operating Position	Swiveling Type
Dimming	Triac Dimming
Construction	Track
Mounting Type	Track Light Structure
Heads	Single Head
Body Material	Aluminium Die cast
Finish	Black
Length	6-1/4"
Height	6-3/4"
Diameter	2-1/2"
Application Area	Indoor Applications

3eam	Sprea	d (Options)	)				
Spot	15°	Medium	24°	Flood	38°	Wide Flo	od 60°
ft	Ø	ft	Ø	ft	Ø	ft	Ø
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75
	Spot ft 3.0 9.0	Spot 15° ft Ø 3.0 0.72 9.0 2.15	Spot 15° Medium ft Ø ft 3.0 0.72 3.0 9.0 2.15 9.0	ft Ø ft Ø 3.0 0.72 3.0 1.41 9.0 2.15 9.0 4.22	Spot 15* Medium 24* Flood   ft Ø ft Ø ft   3.0 0.72 3.0 1.41 3.0   9.0 2.15 9.0 4.22 9.0	Spot 15° Medium 24° Flood 38°   ft Ø ft Ø ft Ø   3.0 0.72 3.0 1.41 3.0 2.03   9.0 2.15 9.0 4.22 9.0 6.09	Spot 15° Medium 24° Flood 38° Wide Flo   ft Ø ft Ø ft Ø ft   3.0 0.72 3.0 1.41 3.0 2.03 3.0   9.0 2.15 9.0 4.22 9.0 6.09 9.0

Trang is a technologically advanced LED track light with incorporated electronic gear and chip on board. It also has a high-quality reflector with three different beam spreads. Moreover, the lamp housing of die-cast aluminum for optimal cooling allows the fixture to last longer than its traditional counterparts.

## **Technical Data**

IES File Link 丛

Installation Instructions Link 🕹

