


Trang Track Lights

ITEM SKU#: 662187492285













Product Code: IK-RTRANGTL-20W-40K-WH-90C-38D

Voltage	100 - 277 V AC, 50-60 Hz		
Lumen Output	2005.55lm		
Power	20W		
Efficacy	140lm/w		
ССТ	4000K		
CRI	>90		
Beam Angle	38°		
Light Distribution	Flood		
LED Type	COB		
LED Light Source	Osram SOLERIQ S 19		
Start Time	Instant		
Driver	Stand Alone (included)		
Operating Position	Swiveling Type		
Dimming	Triac Dimming		
Construction	Track		
Mounting Type	Track Light Structure		
Heads	Single Head		
Body Material	Aluminium Die cast		
Finish	White		
Length	6-1/4"		
Height	6-3/4"		
Diameter	2-1/2"		
Application Area	Indoor Applications		

3eam	Sprea	d (Options))				
Spot	15°	Medium	24°	Flood	38°	Wide Flo	od 60°
ft	Ø	ft	Ø	ft	Ø	ft	Ø
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75
	Spot ft 3.0 9.0	Spot 15° ft Ø 3.0 0.72 9.0 2.15	Spot 15° Medium ft Ø ft 3.0 0.72 3.0 9.0 2.15 9.0	ft Ø ft Ø 3.0 0.72 3.0 1.41 9.0 2.15 9.0 4.22	Spot 15* Medium 24* Flood ft Ø ft Ø ft 3.0 0.72 3.0 1.41 3.0 9.0 2.15 9.0 4.22 9.0	Spot 15° Medium 24° Flood 38° ft Ø ft Ø ft Ø 3.0 0.72 3.0 1.41 3.0 2.03 9.0 2.15 9.0 4.22 9.0 6.09	Spot 15° Medium 24° Flood 38° Wide Flo ft Ø ft Ø ft Ø ft 3.0 0.72 3.0 1.41 3.0 2.03 3.0 9.0 2.15 9.0 4.22 9.0 6.09 9.0

Trang is a technologically advanced LED track light with incorporated electronic gear and chip on board. It also has a high-quality reflector with three different beam spreads. Moreover, the lamp housing of die-cast aluminum for optimal cooling allows the fixture to last longer than its traditional counterparts.

Technical Data

IES File Link 丛

Installation Instructions Link 🕹

