

Bolt

Downlight



Bolt, a cylindrical shaped LED surface downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid /global connectors available with isolated LED Driver using Ultra bright OSRAM COB.

Model/Colors | Available in White & Black.

Application Areas | Downlight For Indoor Applications.
Guest Room, Restaurant, Meeting Room, Club, Hall, Hotel Entrance.

Medium		Flood	
20°		40°	
ft	ø	ft	ø
3.0	1.41	3.0	2.03
9.0	4.22	9.0	6.09
15.0	7.04	15.0	10.15

TECHNICAL PARAMETERS

Voltage	100 - 277 V AC, 50-60 Hz
IP Rating	IP65
Light Source	Osram SOLERIQ S 19
Operating Position	Non Swiveling Type
Start Time	Instant
Driver	Stand Alone (included)
Optics	Reflective Cup Structure
Beam Spread	Spot, Medium, Flood
Dimming	Triac Dimming / 0-10 V Dimming



CRI	Power (W)	CCT (K)	Total Lumen Output (lm)	Beam Spread	Finish
>90	30 W / 40 W / 50 W / 55 W	2700 K	3600 / 4800 / 6000 / 6600	20° / 40°	White / Black
>90	30 W / 40 W / 50 W / 55 W	3000 K	3800 / 5050 / 6320 / 6950	20° / 40°	White / Black
>90	30 W / 40 W / 50 W / 55 W	4000 K	4000 / 5320 / 6650 / 7315	20° / 40°	White / Black
>90	30 W / 40 W / 50 W / 55 W	5000 K	4200 / 5600 / 7000 / 7700	20° / 40°	White / Black

Note

1. Product available in other Kelvin temperatures on request.